

LSQT limit switch box

New **Technopolymer** limit switch box for quarter turn valves combining easy installation with great versatility of use, even in corrosive environments. • **Compact design** with threaded cover • Plastic installation clips and brackets • Protection class **IP67** or higher guaranteed by safety pin insert • **Configurable optical indicator** with high visibility yellow arrows • Label with QR code for digital assistance to installation • Versatility of installation on all models of quarter turn actuators and FIP manual valves



Objednáací číslo	Material	Kategorie	product.detail.attribute.Per utilizzo con valvole serie:	DN
ZMSMEC001	FLS Measurement Instrumentation	Příslušenství pro pohonované armatury	DKM / NO - DA	40 ÷ 65
ZMSMEC002	FLS Measurement Instrumentation	Příslušenství pro pohonované armatury	DKM / NC	40
ZMSMEC003	FLS Measurement Instrumentation	Příslušenství pro pohonované armatury	DKM / NC	50 ÷ 65
ZMSMEC004	FLS Measurement Instrumentation	Příslušenství pro pohonované armatury	VM / NC	80 ÷ 100
ZMSMEC005	FLS Measurement Instrumentation	Příslušenství pro pohonované armatury	VM / NO - DA	80
ZMSMEC006	FLS Measurement Instrumentation	Příslušenství pro pohonované armatury	VM / NO - DA	100

LSQT limit switch box

- Upper part (PVC-U)
 - Bottom part (PVC-U)
 - Bolts (zinc plated steel)
 - Nuts (zinc plated steel)
 - Gasket (NBR)
 - Reinforcing ring (Stainless steel)
- The reinforcing bush are used to reinforce the pipe PE100 (SDR11) e PE-X, to elong the lifetime of the pipeline and to reduce the collapse risk of the pipe in disadvantages conditions. They use is particularly suggested using PE-X pipes. The two tightening keys (d.16-63 and d.75-110) are important tools to install the **MAGNUM 3G** fittings