

Pilot valve "SP/NC"



Objednací číslo	Materiál	Kategorie	product.detail.attribute.To be used with:	product.detail.attribute.Voltage
SPNC014N024AC	FLS Measurement Instrumentation	Příslušenství pro pohonované armatury	DK/CP – DKM/CP – DKP/CP – DKD/CP – VM/CP – CM/CP	24V AC 50 Hz
SPNC014N024DC	FLS Measurement Instrumentation	Příslušenství pro pohonované armatury	DK/CP – DKM/CP – DKP/CP – DKD/CP – VM/CP – CM/CP	24V DC
SPNC014N110AC	FLS Measurement Instrumentation	Příslušenství pro pohonované armatury	DK/CP – DKM/CP – DKP/CP – DKD/CP – VM/CP – CM/CP	110V AC 50 Hz
SPNC014N220AC	FLS Measurement Instrumentation	Příslušenství pro pohonované armatury	DK/CP – DKM/CP – DKP/CP – DKD/CP – VM/CP – CM/CP	220V AC 50 Hz

Pilot valve "SP/NC"

- Upper part (PVC-U)
 - Bottom part (PVC-U)
 - Bolts (zinc plated steel)
 - Nuts (zinc plated steel)
 - Gasket (NBR)
 - Reinforcing ring (Stainless steel)
- The reinforcing bush are used to reinforce the pipe PE100 (SDR11) e PE-X, to elong the lifetime of the pipeline and to reduce the collapse risk of the pipe in disadvantages conditions. They use is particurally suggested using PE-X pipes. The two tightening keys (d.16-63 and d.75-110) are important tools to install the **MAGNUM 3G** fittings