

Pilot valve "SP/NC"



| Objednací číslo | Materiál | Kategorie | product.detail.attribute.To be used with: | product.detail.attribute.Voltage |
|-----------------|---------------------------------|---------------------------------------|--|----------------------------------|
| SPNC014N024AC | FLS Measurement Instrumentation | Příslušenství pro pohonované armatury | DK/CP - DKM/CP - DKP/CP - DKD/CP - VM/CP - CM/CP | 24V AC 50 Hz |
| SPNC014N024DC | FLS Measurement Instrumentation | Příslušenství pro pohonované armatury | DK/CP - DKM/CP - DKP/CP - DKD/CP - VM/CP - CM/CP | 24V DC |
| SPNC014N110AC | FLS Measurement Instrumentation | Příslušenství pro pohonované armatury | DK/CP - DKM/CP - DKP/CP - DKD/CP - VM/CP - CM/CP | 110V AC 50 Hz |
| SPNC014N220AC | FLS Measurement Instrumentation | Příslušenství pro pohonované armatury | DK/CP - DKM/CP - DKP/CP - DKD/CP - VM/CP - CM/CP | 220V AC 50 Hz |



Pilot valve "SP/NC"

- Upper part (PVC-U)
 - Bottom part (PVC-U)
 - Bolts (zinc plated steel)
 - Nuts (zinc plated steel)
 - Gasket (NBR)
 - Reinforcing ring (Stainless steel)
- The reinforcing bush are used to reinforce the pipe PE100 (SDR11) e PE-X, to elong the lifetime of the pipeline and to reduce the collapse risk of the pipe in disadvantages conditions. They use is particularly suggested using PE-X pipes. The two tightening keys (d.16-63 and d.75-110) are important tools to install the **MAGNUM 3G** fittings