


# SSEAV – Easyfit True Union ball and spring check valve

Easyfit spring check valve with female ends for solvent welding, ASTM series



## EPDM

Objednací číslo	Materiál	Kategorie	d	DN	PN	E	H	L	Z	g
FROV040EMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-
FROV050EMLH	PVC-U system	Armatury	1/2"	15	16	54	96	22,5	51	149
FROV063EMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-
FROV075EMLH	PVC-U system	Armatury	3/4"	20	16	63	105	25,5	54	188
FROV090EMLH	PVC-U system	Armatury	1"	25	16	72	117	28,7	59,5	292
FROV110EMLH	PVC-U system	Armatury	1" 1/4	32	16	85	136	32	72	445
FROV140EMLH	PVC-U system	Armatury	1" 1/2	40	16	100	147	35	77	640
FROV160EMLH	PVC-U system	Armatury	2"	50	16	118	174	38,2	97,6	1010
FROV225EMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-
FROV280EMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-
FROV315EMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-
FROV355EMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-
FROV400EMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-

## FKM

Objednací číslo	Materiál	Kategorie	d	DN	PN	E	H	L	Z	g
FROV040FMLH	PVC-U system	Armatury	1/2"	15	16	54	96	22,5	51	149
FROV050FMLH	PVC-U system	Armatury	3/4"	20	16	63	105	25,5	54	188

## SSEAV – Easyfit True Union ball and spring check valve

Objednací číslo	Materiál	Kategorie	d	DN	PN	E	H	L	Z	g
FROV063FMLH	PVC-U system	Armatury	1"	25	16	72	117	28,7	59,5	292
FROV075FMLH	PVC-U system	Armatury	1" 1/4	32	16	85	136	32	72	445
FROV090FMLH	PVC-U system	Armatury	1" 1/2	40	16	100	147	35	77	640
FROV110FMLH	PVC-U system	Armatury	2"	50	16	118	174	38,2	97,6	1010
FROV140FMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-
FROV160FMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-
FROV225FMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-
FROV280FMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-
FROV315FMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-
FROV355FMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-
FROV400FMLH	PVC-U system	Armatury	-	-	-	-	-	-	-	-

# SSEAV – Easyfit True Union ball and spring check valve

- **Customisable Labelling System: built-in LCE module** on the valve body made up of transparent protection plug and customisable tag holder using the LSE set (available as accessory). The customisation potential lets you identify the valve on the system according to specific needs.
- **Optimised dynamic fluid design:** energy savings thanks to the improved valve Kv value with consequent pressure drop reduction
- High surface finish ball shutter: **wear reduction**, increase in working life and reduced valve maintenance. Ideal for conveying dirty fluids, even with suspended solids and filaments thanks to the special design that permits **internal valve selfcleaning**
- **Locked ball seat carrier:** safe dismounting for maintenance with the Easyfit multifunctional handle or Easytorque kit
- Ideal for horizontal installations: **perfect seal even with low back pressure. Silent** and durable even with strong vibrations and pulsating fluid
- PVC-U shutter and springs available made of STAINLESS steel 316, Hastelloy C276, A316 PTFE encapsulated: maximum reliability in a **wide field of applications** from salt water to aggressive acids
  
- Connection system for solvent weld and threaded joints
- **Valve material compatibility (PVC-U)** with water conveyance, drinking water and other food substances according to current regulations
- **PN16 True Union** valve body made for PVC-U injection moulding and European Directive 2014/68/EU (PED) compliant for pressurised equipment. ISO 9393 compliant test requirements
- **Short face to face dimension** according to international regulation ISO 7508 series III and European regulation EN 1452 "short" and fully interchangeable with VXE and VEE DN 10÷50 ball valve models
- Union nuts with rack for tightening adjustment via Easyfit handle or via Easytorque adjustment kit (available as accessories)
- **Vertical** (preferable for SXE model) and **horizontal installation** potential