


SSEAV – Easyfit True Union ball and spring check valve

Easyfit spring check valve with female ends for solvent welding, ASTM series



EPDM

Objednací číslo	Materiál	Kategorie	d	DN	PN	E	H	L	Z	g
FROAM112EMLH	PP-H system	Armatury	1/2"	15	16	54	96	22,5	51	149
FROAM114EMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-
FROAM200EMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-
FROAM212EMLH	PP-H system	Armatury	3/4"	20	16	63	105	25,5	54	188
FROAM300EMLH	PP-H system	Armatury	1"	25	16	72	117	28,7	59,5	292
FROAM400EMLH	PP-H system	Armatury	1" 1/4	32	16	85	136	32	72	445
FROAM500EMLH	PP-H system	Armatury	1" 1/2	40	16	100	147	35	77	640
FROAM600EMLH	PP-H system	Armatury	2"	50	16	118	174	38,2	97,6	1010
FROAM800EMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-
FROAM810EMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-
FROAM812EMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-
FROAM814EMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-
FROAM816EMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-

FKM

Objednací číslo	Materiál	Kategorie	d	DN	PN	E	H	L	Z	g
FROAM112FMLH	PP-H system	Armatury	3/4"	20	16	63	105	25,5	54	188
FROAM114FMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-

SSEAV – Easyfit True Union ball and spring check valve

Objednací číslo	Materiál	Kategorie	d	DN	PN	E	H	L	Z	g
FROAM200FMLH	PP-H system	Armatury	1"	25	16	72	117	28,7	59,5	292
FROAM212FMLH	PP-H system	Armatury	1" 1/4	32	16	85	136	32	72	445
FROAM300FMLH	PP-H system	Armatury	1" 1/2	40	16	100	147	35	77	640
FROAM400FMLH	PP-H system	Armatury	2"	50	16	118	174	38,2	97,6	1010
FROAM500FMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-
FROAM600FMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-
FROAM800FMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-
FROAM810FMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-
FROAM812FMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-
FROAM814FMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-
FROAM816FMLH	PP-H system	Armatury	-	-	-	-	-	-	-	-

SSEAV – Easyfit True Union ball and spring check valve

- **Customisable Labelling System: built-in LCE module** on the valve body made up of transparent protection plug and customisable tag holder using the LSE set (available as accessory). The customisation potential lets you identify the valve on the system according to specific needs.
- **Optimised dynamic fluid design:** energy savings thanks to the improved valve Kv value with consequent pressure drop reduction
- High surface finish ball shutter: **wear reduction**, increase in working life and reduced valve maintenance. Ideal for conveying dirty fluids, even with suspended solids and filaments thanks to the special design that permits **internal valve selfcleaning**
- **Locked ball seat carrier:** safe dismounting for maintenance with the Easyfit multifunctional handle or Easytorque kit
- Ideal for horizontal installations: **perfect seal even with low back pressure. Silent** and durable even with strong vibrations and pulsating fluid
- PVC-U shutter and springs available made of STAINLESS steel 316, Hastelloy C276, A316 PTFE encapsulated: maximum reliability in a **wide field of applications** from salt water to aggressive acids

- Connection system for solvent weld and threaded joints
- **Valve material compatibility (PVC-U)** with water conveyance, drinking water and other food substances according to current regulations
- **PN16 True Union** valve body made for PVC-U injection moulding and European Directive 2014/68/EU (PED) compliant for pressurised equipment. ISO 9393 compliant test requirements
- **Short face to face dimension** according to international regulation ISO 7508 series III and European regulation EN 1452 "short" and fully interchangeable with VXE and VEE DN 10÷50 ball valve models
- Union nuts with rack for tightening adjustment via Easyfit handle or via Easytorque adjustment kit (available as accessories)
- **Vertical** (preferable for SXE model) and **horizontal installation** potential