

S12IV - TRUE UNION 2-WAY SOLENOID VALVE

2 way solenoid valve with female union ends for solvent welding Function: Normally closed



EPDM

| Objednací číslo | Materiál | Kategorie | Série |
|-----------------|---------------------------------|---|------------|
| S12IV0410E230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0412E230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0416E230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0610E230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0612E230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0616E230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0810E230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0812E230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0816E230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |

S12IV - TRUE UNION 2-WAY SOLENOID VALVE

| Objednací číslo | Materiál | Kategorie | Série |
|-----------------|---------------------------------|---|------------|
| S12IV0410F230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0412F230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0416F230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0610F230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0612F230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0616F230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |

S12IV - TRUE UNION 2-WAY SOLENOID VALVE

| Objednací číslo | Materiál | Kategorie | Série |
|-----------------|---------------------------------|---|------------|
| S12IV0810F230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0812F230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |
| S12IV0816F230A | FLS Measurement Instrumentation | Elektricky ovládané pohonované armatury | S1 DN 4÷15 |

S12IV - TRUE UNION 2-WAY SOLENOID VALVE

- Installation flexibility and ease of maintenance: high-performance solenoid electric actuator with internal moving parts designed to exceed 5 million maintenance free operating cycles. Adjustable circular section coil with IP65 protection class.
 - DIN 43650 electrical connector supplied as standard: includes LED indicator light and rectifier (in the case of an AC coil).
 - Lever shutter in EPDM or FKM and lever in stainless steel.
 - Suitable for use with aggressive fluids: no metal component in contact with the fluid or the external environment; all the screws are covered by PE protection plugs.
 - Emergency override
-
- 2-Way PVC-U body
 - Installation flexibility and ease of maintenance: high-performance solenoid electric actuator designed to exceed 5 million maintenance-free operating cycles
 - Adjustable circular section coil with IP65 protection class.
 - Integrated override with the possibility of being installed in 3 different positions.
 - Lever shutter in EPDM or FKM and lever in stainless steel.
 - DIN 43650 electrical connector supplied as standard: includes LED indicator light and rectifier (in the case of an AC coil).