

M9.07.PX – M9.07.WX

Conductivity and Flow Monitor and Transmitter



Objednáací číslo	product.detail.attribute.Mounting	product.detail.attribute.Power supply	product.detail.attribute.Wire power Technology	product.detail.attribute.Sensor Input
M9.07.P1	Panel	12 – 24 VCC	3/4 wire	Conductivity \$ temperature \$ Flow (Frequency)
M9.07.W1	Wall	12 – 24 VCC	3/4 wire	Conductivity \$ temperature \$ Flow (Frequency)
M9.07.W2	Wall	110 – 230 VCA	3/4 wire	Conductivity \$ temperature \$ Flow (Frequency)

M9.07.PX – M9.07.WX

- APPLICATIONS • Water treatment and regeneration • Industrial waste water treatment and recovery • Softener process • Filtration systems • Desalination process • Demineralized water production • Reverse osmosis process • Cooling water monitoring • Processing and manufacturing industry • Chemical production MAIN FEATURES • Wide full graphic display • Multicolor backlight • Help on board • Simultaneous measurement of conductivity, temperature and flow • Fast, intuitive and mistake-proof calibration software • Mechanical relay for external device control • Solid State Relays for programmable alarms • Multilanguage menus • USB port for software upgrading