


CMFM/CP DA - PNEUMATICALLY ACTUATED COMPACT DIAPHRAGM VALVE WITH PISTON ACTUATOR DN 12:15

Pneumatically actuated compact diaphragm valve with BS parallel socket threaded ends, Double Acting.



EPDM

Objednací číslo	product.detail.attribute.R	DN	PN	product.detail.attribute.Ra	L	H	product.detail.attribute.h	product.detail.attribute.J	g
CMFM DA038E	3/8"	12	6	G 1/4"	12	75	8	M5	300
CMFM DA012E	1/2"	15	6	G 1/4"	15	75	8	M5	300

FKM

Objednací číslo	product.detail.attribute.R	DN	PN	product.detail.attribute.Ra	L	H	product.detail.attribute.h	product.detail.attribute.J	g
CMFM DA038F	3/8"	12	6	G 1/4"	12	75	8	M5	300
CMFM DA012F	1/2"	15	6	G 1/4"	15	75	8	M5	300

PTFE

Objednací číslo	product.detail.attribute.R	DN	PN	product.detail.attribute.Ra	L	H	product.detail.attribute.h	product.detail.attribute.J	g
CMFM DA038P	3/8"	12	6	G 1/4"	12	75	8	M5	300
CMFM DA012P	1/2"	15	6	G 1/4"	15	75	8	M5	300

CMFM/CP DA – PNEUMATICALLY ACTUATED COMPACT DIAPHRAGM VALVE WITH PISTON ACTUATOR DN 12:15

The new compact and light piston actuator in PP-GR makes the CM/CP the ideal choice for applications requiring very frequent valve operation and a long valve lifetime.

- Compact and lightweight piston actuator in PP-GR, free of exposed metallic parts, particularly suited for use in severe environmental and chemically aggressive conditions.
- High strength IXEF piston guarantees high reliability over time without maintenance.
- High visibility graduated optical position indicator protected by a transparent cap with a seal O-Ring.
- The valve is impervious to fluids containing impurities
- It has an high flow rate
- It can be installed in any position
- It has an extremely compact structure
- It is actuated by a dry running piston and does not require maintenance
- It has no protruding screws and is fully free of impurity deposits
- Allows for an easy diaphragm seal replacement
- The Standard version valve comes with a position indicator.