


FCIV-Trogamid

Float: AISI 316 Stainless Steel



Objednací číslo	Material	Kategorie	Série	D	product.detail.attribute.Flow rate range for H ₂ O [l/h]	B	E	C
FCIV016D1X0030	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	16	3 - 30	199	165	171
FCIV016D1X0040	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	16	4 - 40	199	165	171
FCIV016D1X0100	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	16	10 - 100	199	165	171
FCIV016D1X0200	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	16	20 - 200	199	165	171
FCIV016D1X0300	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	16	30 - 300	199	165	171
FCIV020D1X0050	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	20	5 - 50	208	170	176
FCIV020D1X0100	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	20	10 - 100	208	170	176
FCIV020D1X0160	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	20	15 - 160	208	170	176
FCIV020D1X0250	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	20	20 - 250	208	170	176
FCIV020D1X0350	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	20	35 - 350	208	170	176
FCIV020D1X0600	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	20	60 - 600	208	170	176
FCIV025D1X0150	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	25	15 - 150	229	185	191
FCIV025D1X0250	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	25	25 - 250	229	185	191

FCIV-Trogamid

Objednačí číslo	Materiál	Kategorie	Série	D	product.detail.attribute.Flow rate range for H ₂ O [l/h]	B	E	C
FCIV025D1X0400	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	25	40 - 400	229	185	191
FCIV025D1X0600	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	25	50 - 600	229	185	191
FCIV025D1X1100	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	25	100 - 1100	229	185	191
FCIV032D1X0400	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	32	40 - 400	250	200	206
FCIV032D1X0600	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	32	50 - 600	250	200	206
FCIV032D1X1000	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	32	100 - 1000	250	200	206
FCIV032D1X1500	Flowmeters	Compact flowmeters	H ₂ O Scale - SS Float	32	150 - 1500	250	200	206

FCIV-Trogamid

- Metering tubes are available in Trogamid (PA) suitable for most inert media, PVC-U suitable for slight corrosive media and Polysulfone (PSU) suitable for corrosive media on an extended operating temperature range. End connectors available in PVC-U, PVC-C, PP, SS, Malleable Cast Iron. Male threads moulded onto the end of the metering tube are used for easy mounting of unions. Standard unions are in PVC-U but others are available according to the different working conditions; Metal unions widen the range of operating conditions such as pressure and temperature. The floats are available in Stainless Steel AISI 316 and in PP to match the proper chemical compatibility with the flow medium and to offer different measuring ranges. Magnetic Float option is available to be combined with micro switches for MIN and MAX alarm, clamped on the guide of the flowmeter. The micro switches, housing a bistable reed contact are activated by the passage of the magnet incorporated into the float. Flowmeters body are equipped with a double guide allowing the installation of two alarm in a very close position. Double scale option available for specific application requirements to customize measuring units for an easy conversion or comprehension of the flow rate values.
- • Wide choice of measuring scales: water scale from 1,5 to 50.000 l/h, HCl scale from 1,4 to 23.000 l/h, NaOH 30% scale from 0,25 to 43.000 l/h, NaOH 50% scale from 0,025 to 40.000 l/h, Air scale from 0,025 to 500 Nm³/h • Wide choice of end connections available in PVC-U, PVC-C, PP-H, AISI 316 SS, Carbon Steel • Eight different diameters • Three different plastic tube materials: PA, PVC and PSU • Float materials available in SS and PP, with or without magnet • High level of accuracy: FS accuracy class 2,5; FC accuracy class 4 • Simple operation and very limited maintenance. • Other engineering units like LPM, m³/h or % together with double scales and special scales are available on request.