

FCFV-Polysulfone+magnet

Float: AISI 316 Stainless Steel + Magnet



Objednací číslo	Materiál	Kategorie	Série	product.detail.attribute.R	product.detail.attribute.Flow rate range for H[5:2]O [l/h]	B	E	C
FCFV012P1X0050M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	1/2" "	5 - 50	212	176	170
FCFV012P1X0100M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	1/2" "	10 - 100	212	176	170
FCFV012P1X0160M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	1/2" "	15 - 160	212	176	170
FCFV012P1X0250M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	1/2" "	20 - 250	212	176	170
FCFV012P1X0350M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	1/2" "	35 - 350	212	176	170
FCFV012P1X0600M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	1/2" "	60 - 600	212	176	170
FCFV034P1X0150M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	3/4" "	15 - 150	232	191	185
FCFV034P1X0250M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	3/4" "	25 - 250	232	191	185
FCFV034P1X0400M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	3/4" "	40 - 400	232	191	185

FCFV-Polysulfone+magnet

Objednačí číslo	Materiál	Kategorie	Série	product.detail.attribute.R	product.detail.attribute.Flow rate range for H[5:2]O [l/h]	B	E	C
FCFV034P1X0600M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	3/4"	50 - 600	232	191	185
FCFV034P1X1100M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	3/4"	100 - 1100	232	191	185
FCFV038P1X0030M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	3/8"	3 - 30	198	171	165
FCFV038P1X0040M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	3/8"	4 - 40	198	171	165
FCFV038P1X0100M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	3/8"	10 - 100	198	171	165
FCFV038P1X0200M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	3/8"	20 - 200	198	171	165
FCFV038P1X0300M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	3/8"	30 - 300	198	171	165
FCFV100P1X0400M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	1"	40 - 400	251	206	200
FCFV100P1X0600M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	1"	50 - 600	251	206	200
FCFV100P1X1000M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	1"	100 - 1000	251	206	200
FCFV100P1X1500M	Flowmeters	Compact flowmeters	H2O Scale - SS Float	1"	150 - 1500	251	206	200

FCFV-Polysulfone+magnet

- Metering tubes are available in Trogamid (PA) suitable for most inert media, PVC-U suitable for slight corrosive media and Polysulfone (PSU) suitable for corrosive media on an extended operating temperature range. End connectors available in PVC-U, PVC-C, PP, SS, Malleable Cast Iron. Male threads moulded onto the end of the metering tube are used for easy mounting of unions. Standard unions are in PVC-U but others are available according to the different working conditions; Metal unions widen the range of operating conditions such as pressure and temperature. The floats are available in Stainless Steel AISI 316 and in PP to match the proper chemical compatibility with the flow medium and to offer different measuring ranges. Magnetic Float option is available to be combined with micro switches for MIN and MAX alarm, clamped on the guide of the flowmeter. The micro switches, housing a bistable reed contact are activated by the passage of the magnet incorporated into the float. Flowmeters body are equipped with a double guide allowing the installation of two alarm in a very close position. Double scale option available for specific application requirements to customize measuring units for an easy conversion or comprehension of the flow rate values.
- Wide choice of measuring scales: water scale from 1,5 to 50.000 l/h, HCl scale from 1,4 to 23.000 l/h, NaOH 30% scale from 0,25 to 43.000 l/h, NaOH 50% scale from 0,025 to 40.000 l/h, Air scale from 0,025 to 500 Nm³/h • Wide choice of end connections available in PVC-U, PVC-C, PP-H, AISI 316 SS, Carbon Steel • Eight different diameters • Three different plastic tube materials: PA, PVC and PSU • Float materials available in SS and PP, with or without magnet • High level of accuracy: FS accuracy class 2,5; FC accuracy class 4 • Simple operation and very limited maintenance. • Other engineering units like LPM, m³/h or % together with double scales and special scales are available on request.