


FCIV-Polysulfone

Float: PP (Polypropylene) red



Objednací číslo	Materiál	Kategorie	Série	D	product.detail.attribute.Flow rate range for H[5:2]O [l/h]	B	E	C
FCIV016P1M0015	Flowmeters	Compact flowmeters	H2O Scale - PP Float	16	1,5 - 15	199	165	171
FCIV016P1M0020	Flowmeters	Compact flowmeters	H2O Scale - PP Float	16	2 - 20	199	165	171
FCIV016P1M0050	Flowmeters	Compact flowmeters	H2O Scale - PP Float	16	5 - 50	199	165	171
FCIV016P1M0100	Flowmeters	Compact flowmeters	H2O Scale - PP Float	16	10 - 100	199	165	171
FCIV016P1M0150	Flowmeters	Compact flowmeters	H2O Scale - PP Float	16	15 - 150	199	165	171
FCIV020P1M0025	Flowmeters	Compact flowmeters	H2O Scale - PP Float	20	2 - 25	208	170	176
FCIV020P1M0050	Flowmeters	Compact flowmeters	H2O Scale - PP Float	20	5 - 50	208	170	176
FCIV020P1M0100	Flowmeters	Compact flowmeters	H2O Scale - PP Float	20	10 - 100	208	170	176
FCIV020P1M0150	Flowmeters	Compact flowmeters	H2O Scale - PP Float	20	15 - 150	208	170	176
FCIV020P1M0200	Flowmeters	Compact flowmeters	H2O Scale - PP Float	20	20 - 200	208	170	176
FCIV020P1M0320	Flowmeters	Compact flowmeters	H2O Scale - PP Float	20	30 - 320	208	170	176
FCIV025P1M0080	Flowmeters	Compact flowmeters	H2O Scale - PP Float	25	8 - 80	229	185	191
FCIV025P1M0150	Flowmeters	Compact flowmeters	H2O Scale - PP Float	25	15 - 150	229	185	191

FCIV-Polysulfone

Objednačí číslo	Materiál	Kategorie	Série	D	product.detail.attribute.Flow rate range for H ₂ O [l/h]	B	E	C
FCIV025P1M0200	Flowmeters	Compact flowmeters	H ₂ O Scale - PP Float	25	20 - 200	229	185	191
FCIV025P1M0350	Flowmeters	Compact flowmeters	H ₂ O Scale - PP Float	25	30 - 350	229	185	191
FCIV025P1M0650	Flowmeters	Compact flowmeters	H ₂ O Scale - PP Float	25	50 - 650	229	185	191
FCIV032P1M0200	Flowmeters	Compact flowmeters	H ₂ O Scale - PP Float	32	20 - 200	250	200	206
FCIV032P1M0300	Flowmeters	Compact flowmeters	H ₂ O Scale - PP Float	32	30 - 300	250	200	206
FCIV032P1M0600	Flowmeters	Compact flowmeters	H ₂ O Scale - PP Float	32	60 - 600	250	200	206
FCIV032P1M1000	Flowmeters	Compact flowmeters	H ₂ O Scale - PP Float	32	100 - 1000	250	200	206

FCIV-Polysulfone

- Metering tubes are available in Trogamid (PA) suitable for most inert media, PVC-U suitable for slight corrosive media and Polysulfone (PSU) suitable for corrosive media on an extended operating temperature range. End connectors available in PVC-U, PVC-C, PP, SS, Malleable Cast Iron. Male threads moulded onto the end of the metering tube are used for easy mounting of unions. Standard unions are in PVC-U but others are available according to the different working conditions; Metal unions widen the range of operating conditions such as pressure and temperature. The floats are available in Stainless Steel AISI 316 and in PP to match the proper chemical compatibility with the flow medium and to offer different measuring ranges. Magnetic Float option is available to be combined with micro switches for MIN and MAX alarm, clamped on the guide of the flowmeter. The micro switches, housing a bistable reed contact are activated by the passage of the magnet incorporated into the float. Flowmeters body are equipped with a double guide allowing the installation of two alarm in a very close position. Double scale option available for specific application requirements to customize measuring units for an easy conversion or comprehension of the flow rate values.
- • Wide choice of measuring scales: water scale from 1,5 to 50.000 l/h, HCl scale from 1,4 to 23.000 l/h, NaOH 30% scale from 0,25 to 43.000 l/h, NaOH 50% scale from 0,025 to 40.000 l/h, Air scale from 0,025 to 500 Nm³/h • Wide choice of end connections available in PVC-U, PVC-C, PP-H, AISI 316 SS, Carbon Steel • Eight different diameters • Three different plastic tube materials: PA, PVC and PSU • Float materials available in SS and PP, with or without magnet • High level of accuracy: FS accuracy class 2,5; FC accuracy class 4 • Simple operation and very limited maintenance. • Other engineering units like LPM, m³/h or % together with double scales and special scales are available on request.