


SSEBEV - Easyfit True Union ball and spring check valve

Easyfit spring check valve with PE100 SDR 11 male end connectors for butt welding or electrofusion (CVDE)



EPDM

Objednací číslo	Materiál	Kategorie	Série	d	DN	E	H	L	Z	g
SSEBEV020E	PVC-U system	Armatury	SXE-SSE DN 10÷50	20	15	54	154	40,5	73	151
SSEBEV025E	PVC-U system	Armatury	SXE-SSE DN 10÷50	25	20	63	186	54	81	223
SSEBEV032E	PVC-U system	Armatury	SXE-SSE DN 10÷50	32	25	72	199	56	91	302
SSEBEV040E	PVC-U system	Armatury	SXE-SSE DN 10÷50	40	32	85	217	56	109	470
SSEBEV050E	PVC-U system	Armatury	SXE-SSE DN 10÷50	50	40	100	236	60,5	125	665
SSEBEV063E	PVC-U system	Armatury	SXE-SSE DN 10÷50	63	50	118	268	65,5	145	1080

FKM

Objednací číslo	Materiál	Kategorie	Série	d	DN	E	H	L	Z	g
SSEBEV020F	PVC-U system	Armatury	SXE-SSE DN 10÷50	20	15	54	154	40,5	73	151
SSEBEV025F	PVC-U system	Armatury	SXE-SSE DN 10÷50	25	20	63	189	54	81	223
SSEBEV032F	PVC-U system	Armatury	SXE-SSE DN 10÷50	32	25	72	203	56	91	302
SSEBEV040F	PVC-U system	Armatury	SXE-SSE DN 10÷50	40	32	85	221	56	109	470
SSEBEV050F	PVC-U system	Armatury	SXE-SSE DN 10÷50	50	40	100	246	60,5	125	665
SSEBEV063F	PVC-U system	Armatury	SXE-SSE DN 10÷50	63	50	118	276	65,5	145	1080

SSEBEV – Easyfit True Union ball and spring check valve

- **Customisable Labelling System:** built-in LCE module on the valve body made up of transparent protection plug and customisable tag holder using the LSE set (available as accessory). The customisation potential lets you identify the valve on the system according to specific needs.
- **Optimised dynamic fluid design:** energy savings thanks to the improved valve Kv value with consequent pressure drop reduction
- High surface finish ball shutter: **wear reduction**, increase in working life and reduced valve maintenance. Ideal for conveying dirty fluids, even with suspended solids and filaments thanks to the special design that permits **internal valve selfcleaning**
- **Locked ball seat carrier:** safe dismounting for maintenance with the Easyfit multifunctional handle or Easytorque kit
- Ideal for horizontal installations: **perfect seal even with low back pressure. Silent** and durable even with strong vibrations and pulsating fluid
- PVC-U shutter and springs available made of STAINLESS steel 316, Hastelloy C276, A316 PTFE encapsulated: maximum reliability in a **wide field of applications** from salt water to aggressive acids
- Connection system for solvent weld and threaded joints
- **Valve material compatibility (PVC-U)** with water conveyance, drinking water and other food substances according to current regulations
- **PN16 True Union** valve body made for PVC-U injection moulding and European Directive 2014/68/EU (PED) compliant for pressurised equipment. ISO 9393 compliant test requirements
- **Short face to face dimension** according to international regulation ISO 7508 series III and European regulation EN 1452 "short" and fully interchangeable with VXE and VEE DN 10÷50 ball valve models
- Union nuts with rack for tightening adjustment via Easyfit handle or via Easytorque adjustment kit (available as accessories)
- **Vertical** (preferable for SXE model) and **horizontal installation** potential